

## Rapid Cleaner

### DESCRIPTION

Rapid Cleaner is a combination of selected acetone-free solvents for the rapid, efficient cleaning and degreasing of structural components in motor vehicles and industrial applications. The low surface tension of this product means that Rapid Cleaner has excellent penetration properties and therefore easily dissolves oil, grease, resin and tar residues and contaminants, even in hidden areas. After the solvent has evaporated, the surface that remains is free from grease and residues.

### PROPERTIES

- low surface tension
- good penetration
- controlled evaporation free of residues
- dissolves resin and tar-type residues
- removes oil and grease based contaminants
- leaves no residues
- high proportion (97 %) of active components
- contains no chlorine or acetone
- economical to use
- universal application

### TECHNICAL DATA

Basis	: mixture of solvents/no acetone
Colour	: clear/colourless
Form	: liquid, aerosol
Density	: 0.71 g/cm <sup>3</sup>
Flash point	: < 21 °C
Propellant	: CO <sub>2</sub>

### APPLICATION

Because of its universal application, Rapid Cleaner has many areas of use in industry, the workshop and agriculture and for hobbies etc.


#### Brakes

Drum and disc brakes, linings, shoes, cylinders, springs and pads

#### Clutch

Clutch lining, pressure plate and clutch components in general

.../2



# PRODUKTINFORMATION



-2-

## Transmission

Automatic gear change, planet-wheel carriers, oil pump, brake bands, couplings and gearwheels

## Assembly and repair

Carburettor, petrol pump, engine components, electrical system such as controllers, generator/alternator, starter and removes oil and grease spots from floor coverings, materials and linings.

## INSTRUCTIONS

Spray contaminated components and allow to drain. After the solvent has evaporated, the components will be clean and free from grease.


**Product may attack paints and plastic components. Check for compatibility before using.**

## AVAILABLE PACK SIZE

Rapid Cleaner	500 ml	Part No. 3318 D-GB-I-E-P
	500 ml	Part No. 2395 D-F-I
	500 ml	Part No. 1816 D-NL-F-GR-ARAB

PI 03/04/10

**Our information is based on thorough research and may be considered reliable, although not legally binding.**



LIQUI MOLY GMBH  
Jerg-Wieland-Str. 4  
D-89081 Ulm-Lehr

Postfach 28 29  
D-89018 Ulm  
www.liqui-moly.de

Phone: +49-(0)731/1420-13  
Fax: +49-(0)731/1420-82  
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230  
Technische Hotline: +49-(0)731/1420-13