Auspuff-Reparatur-Paste
(Exhaust Repair Paste)

DESCRIPTION

Exhaust Repair Paste has been developed for carrying out quick, simple and economical repairs to exhaust systems. The Exhaust Repair Paste does not contain asbestos or solvent, does not pollute the environment, is heat resistant and provides a gas-tight seal to small holes and cracks in exhaust systems.

PROPERTIES

- quick, simple and economical repairs
- does not contain asbestos or solvents
- very heat resistant
- provides a gas-tight seal to exhaust systems
- simple to use
- no dismantling or welding work necessary

TECHNICAL DATA

Form	: paste-like	
Basis	: inorganic materials	
Colour	: dark grey	
Density at 15 °C	: approx. 1.57	g/cm³
pH-value	: approx. 10	
Odour	: odourless	
Solubility	: insoluble	
Heat resistance	: approx. 700	°C
Storage	: approx. 1 year well sealed in its original container, stored in a cool and frost-free area	

APPLICATION

Used for eliminating leaks and sealing small holes and cracks in exhaust systems.

INSTRUCTIONS

Thoroughly clean dirt and rust from the parts to be treated. Allow the engine to run until the exhaust system has heated up.

Moisten the place to be repaired and the Exhaust Repair Paste and press paste into the damaged area. Smooth down the moistened paste. The paste is hardened by heat radiating from the exhaust system or from the engine idling.

AVAILABLE PACK SIZE

Exhaust Repair Paste	200 g	Part no. 3340

PI 01/02/01

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13