

Fully Synthetic Gear Oil SAE 75W-90

DESCRIPTION

Our fully synthetic gear oil is a high-performance, high-pressure gear oil for high-load manual, auxiliary, transaxle and hypoid transmissions which require a lubricant according to API GL 5. High-quality, fully synthetic base oils and modern additive technology guarantee a wide application range for this oil as well as optimum transmission lubrication under extreme conditions.

PROPERTIES

- wide viscosity range
- outstanding wear protection
- optimum high-pressure properties
- high rust and corrosion protection
- low manual shifting effort
- reduces transmission noise

Specifications / Approvals:

API GL 5
MIL-L-2105 C/D

TECHNICAL DATA

Viscosity class	:	75W-90
ASTM colour	:	1.0
Density at 20 °C	:	0.87 g/cm ³
Viscosity index	:	185
Flash point	:	184 °C
Pour point	:	-43 °C

APPLICATION

For extremely high-load manual, auxiliary, transaxle and hypoid transmissions.

INSTRUCTIONS

The requirements of the vehicle and transmission manufacturers must be adhered to. Miscible with any mineral-base oil residues remaining during oil changes in transmissions and axle drives. Must be disposed of with standard used oil.

AVAILABLE PACK SIZE

Fully synthetic Gear Oil SAE 75W-90	500 ml	Part no. 1413 D-GB-I-E-P
	1 l	Part no. 1414 D-GB-I-E-P
	1 l	Part no. 1950 D-RUS-UA
	1 l	Part no. 2183 D-PL-H-RO-TR
	1 l	Part no. 8967 D-NL-F-GR-ARAB
	20 l	Part no. 1415 D
	60 l	Part no. 1412 D
	205 l	Part no. 1411 D

PI 30/05/08

Our information is based on thorough research and may be considered reliable, although not legally binding.

