

Gear Oil SAE 85W-90

DESCRIPTION

Gear Oil SAE 85W-90 is a high-performance, high-pressure gear oil manufactured from carefully selected base oils and multifunctional additives. It can be used universally in all types of transmissions (spur-gear, bevel-gear and worm-gear transmissions) according to API classification GL 4.

PROPERTIES

- high pressure-absorption capability
- limits wear
- reduces running noise
- excellent viscosity/temperature properties
- excellent ageing resistance
- compatible with sealing materials

Specifications / Approvals:


API GL 4
MAN 341Typ Z2
MAN 341Typ E1
ZF-TE-ML 02B, 16A, 17A, 19A
MIL-L 2105

TECHNICAL DATA

Viscosity class	: 85W-90
Density at 15 °C	: 0.910 g/cm ³
Viscosity at 40 °C	: 210 mm ² /s
Viscosity at 100 °C	: 17.5 mm ² /s
Viscosity index	: 92
Flash point	: 214 °C
Pour point	: -22 °C
ASTM colour	: 5

APPLICATION

For transmissions (particularly manual transmissions) and axle drives with normal to high loading for which an API GL 4 gear oil is required.



PRODUKTTINFORMATION



INSTRUCTIONS

During selection, keep to the viscosity class stipulated by the transmission manufacturer. Miscible with all branded gear oils. Fully effective only when used alone.

AVAILABLE PACK SIZE

Touring High Tech Gear Oil
SAE 80W-90

500 ml	Part no. 1403 D-GB-I-E-P
1 l	Part no. 1030 D-GB-I-E-P
1 l	Part no. 1954 D-RUS-UA
1 l	Part no. 8954 D-NL-F-GR-ARAB
20 l	Part no. 1045 D
60 l	Part no. 1034 D
205 l	Part no. 1038 D
bulk oil	Part no. 1026

PI 12/10/11

Our information is based on thorough research and may be considered reliable, although not legally binding.

