

Page 1 of 13  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 24.01.2013 / 0002  
Replaces revision of / Version: 25.04.2012 / 0001  
Valid from: 24.01.2013  
PDF print date: 24.01.2013  
Dieselpartikelfilter Schutz 250 mL Art.: 5148

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Dieselpartikelfilter Schutz 250 mL**  
**Art.: 5148**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

See definition of the substance or mixture.

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr  
Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

#### 1.4 Emergency telephone

##### Emergency information services / official advisory body:

##### Telephone number of the company in case of emergencies:

Tel.: (+49) 0731-1420-0

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### 2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Not determined

##### 2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

Xn, Harmful, R65  
R66

#### 2.2 Label elements

##### 2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not determined

##### 2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments)

Symbols: Xn

Indications of danger:

Harmful

R-phrases:

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

S-phrases:

2 Keep out of the reach of children.



GB

Page 2 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 24.01.2013 / 0002  
 Replaces revision of / Version: 25.04.2012 / 0001  
 Valid from: 24.01.2013  
 PDF print date: 24.01.2013  
 Dieselpartikelfilter Schutz 250 mL Art.: 5148

23 Do not breathe vapour.  
 24 Avoid contact with skin.  
 35 This material and its container must be disposed of in a safe way.  
 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.  
 Additions:  
 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)</b>	
<b>Registration number (REACH)</b>	01-2119473977-17-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	919-164-8 (REACH-IT List-No.)
<b>CAS</b>	(64742-82-1)
<b>content %</b>	80-100
<b>Classification according to Directive 67/548/EEC</b>	Harmful, Xn, R65 R66
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304 Aquatic Chronic 3, H412

<b>Xylene (mixture of isomers)</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119488216-32-XXXX
<b>Index</b>	601-022-00-9
<b>EINECS, ELINCS, NLP</b>	215-535-7
<b>CAS</b>	CAS 1330-20-7
<b>content %</b>	1-5
<b>Classification according to Directive 67/548/EEC</b>	Flammable, R10 Harmful, Xn, R20/21 Irritant, Xi, R36/37/38 Harmful, Xn, R65
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373

<b>Ferrocene</b>	
<b>Registration number (REACH)</b>	--
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	203-039-3
<b>CAS</b>	CAS 102-54-5
<b>content %</b>	0,1-<1
<b>Classification according to Directive 67/548/EEC</b>	Highly flammable, F, R11 Harmful, Xn, R22 Dangerous for the environment, N, R51-53
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Sol. 1, H228 Acute Tox. 4, H302 Aquatic Chronic 2, H411

Page 3 of 13  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 24.01.2013 / 0002  
Replaces revision of / Version: 25.04.2012 / 0001  
Valid from: 24.01.2013  
PDF print date: 24.01.2013  
Dieselpartikelfilter Schutz 250 mL Art.: 5148

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.  
If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.  
Danger of aspiration  
In case of vomiting, keep head low so that the stomach content does not reach the lungs.  
Immediate admittance to a hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Product removes fat.  
Drying of the skin.  
Dermatitis (skin inflammation)  
Ingestion:  
Nausea  
Vomiting  
Danger of aspiration  
Oedema of the lungs  
Chemical pneumonitis (condition similar to pneumonia)  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.  
Subsequent observation for pneumonia and pulmonary oedema.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray/foam/CO<sub>2</sub>/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Toxic gases  
Flammable vapour/air mixtures

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 24.01.2013 / 0002  
 Replaces revision of / Version: 25.04.2012 / 0001  
 Valid from: 24.01.2013  
 PDF print date: 24.01.2013  
 Dieselpartikelfilter Schutz 250 mL Art.: 5148

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.  
 Ensure sufficient supply of air.  
 Avoid inhalation, and contact with eyes or skin.  
 If applicable, caution - risk of slipping

### 6.2 Environmental precautions

If leakage occurs, dam up.  
 Resolve leaks if this possible without risk.  
 Prevent surface and ground-water infiltration, as well as ground penetration.  
 Prevent from entering drainage system.  
 If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.  
 Fill the absorbed material into lockable containers.  
 Do not wash away with water or watery cleaning agents.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Avoid inhalation of the vapours.  
 Keep away from sources of ignition - Do not smoke.  
 Take measures against electrostatic charging, if appropriate.  
 Avoid contact with eyes or skin.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Under all circumstances prevent penetration into the soil.  
 Do not store with oxidizing agents.  
 Store in a well ventilated place.  
 Protect from direct sunlight and warming.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Content %:80-100
WEL-TWA: 1000 mg/m <sup>3</sup>	WEL-STEL: ---	---

GB

Page 5 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 24.01.2013 / 0002  
 Replaces revision of / Version: 25.04.2012 / 0001  
 Valid from: 24.01.2013  
 PDF print date: 24.01.2013  
 Dieselpartikelfilter Schutz 250 mL Art.: 5148

BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)
-----------	---------------------------------------------------

Chemical Name	Xylene (mixture of isomers)		Content %:1-5
WEL-TWA: 50 ppm (220 mg/m <sup>3</sup> ) (WEL), 50 ppm (221 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 100 ppm (441 mg/m <sup>3</sup> ) (WEL), 100 ppm (442 mg/m <sup>3</sup> ) (EU)	---	
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Xylene (mixture of isomers)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg bw/day	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Solvent resistant protective gloves (EN 374).  
 If applicable  
 Protective nitrile gloves (EN 374)  
 Protective Viton gloves (EN 374)  
 Protective hand cream recommended.

Skin protection - Other:

Page 6 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 24.01.2013 / 0002  
 Replaces revision of / Version: 25.04.2012 / 0001  
 Valid from: 24.01.2013  
 PDF print date: 24.01.2013  
 Dieselpartikelfilter Schutz 250 mL Art.: 5148

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:  
 If OES or MEL is exceeded.  
 Gas mask filter A (EN 14387), code colour brown  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Orange, Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	58 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,6 Vol-% ((Particulars of main substances contained) )
Upper explosive limit:	6,1 Vol-% ((Particulars of main substances contained) )
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,8069 g/ml (15°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<7 mm <sup>2</sup> /s (40°C)
Explosive properties:	Not determined
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 24.01.2013 / 0002

Replaces revision of / Version: 25.04.2012 / 0001

Valid from: 24.01.2013

PDF print date: 24.01.2013

Dieselpartikelfilter Schutz 250 mL Art.: 5148

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Electrostatic charge

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

### Dieselpartikelfilter Schutz 250 mL

Art.: 5148

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	~3400	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	13100	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizing
Germ cell mutagenicity:						Negative
Carcinogenicity:						Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						No (inhalation)
Aspiration hazard:						Yes

GB

Page 8 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 24.01.2013 / 0002  
 Replaces revision of / Version: 25.04.2012 / 0001  
 Valid from: 24.01.2013  
 PDF print date: 24.01.2013  
 Dieselpartikelfilter Schutz 250 mL Art.: 5148

Symptoms:						dizziness, unconsciousness, headaches
-----------	--	--	--	--	--	---------------------------------------------

Xylene (mixture of isomers)						
Toxicity/effect	Endpoint t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	2000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Irritant
Serious eye damage/irritation:				Rabbit		Irritant
Respiratory or skin sensitisation:					(Patch-Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						Yes
Respiratory tract irritation:						Irritation of the respiratory tract
Symptoms:						breathing difficulties, drying of the skin., dizziness, unconsciousness, burning of the membranes of the nose and throat, vomiting, skin afflictions, heart/circulatory disorders, coughing, headaches, drowsiness, dizziness, nausea

Ferrocene						
Toxicity/effect	Endpoint t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1320	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	832	mg/kg	Mouse		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Serious eye damage/irritation:						Mild irritant
Symptoms:						respiratory distress, coughing, mucous membrane irritation

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Dieselpartikelfilter Schutz 250 mL Art.: 5148							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment:							n.d.a.
Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)**



Page 9 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 24.01.2013 / 0002  
 Replaces revision of / Version: 25.04.2012 / 0001  
 Valid from: 24.01.2013  
 PDF print date: 24.01.2013  
 Dieselpartikelfilter Schutz 250 mL Art.: 5148

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LL50	96h	>10- <100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	EL50	48h	100-200	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to daphnia:	NOEC/NO EL	21d	0,28	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
Toxicity to algae:	EL50	72h	10-100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:		28d	74,7	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Bioaccumulative potential:	Log Pow		4,2-7,2				
Results of PBT and vPvB assessment:							No PBT substance, No vPvB substance

Xylene (mixture of isomers)							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	20,9	mg/l	Lepomis macrochirus		
Toxicity to daphnia:	EC50	48h	1	mg/l	Daphnia magna		
Toxicity to algae:	IC50	72h	2,2	mg/l			
Persistence and degradability:			>60	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Bioaccumulative potential:	BCF		25,9				
Bioaccumulative potential:	Log Pow		3				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Results of PBT and vPvB assessment:							n.a.
Water solubility:			9	g/l			25°C

Ferrocene							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	24,5	mg/l			
Toxicity to daphnia:	NOEC/NO EL	21d	<0,002	mg/l	Daphnia magna		
Toxicity to daphnia:	EC50	48h	1,5-2,6	mg/l			
Toxicity to algae:	EC50	72h	2,4-3,8	mg/l			
Persistence and degradability:		28d	60	%			Not readily but inherent biodegradable.
Bioaccumulative potential:	Log Pow		3,28				

### SECTION 13: Disposal considerations

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 24.01.2013 / 0002  
 Replaces revision of / Version: 25.04.2012 / 0001  
 Valid from: 24.01.2013  
 PDF print date: 24.01.2013  
 Dieselpartikelfilter Schutz 250 mL Art.: 5148

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

13 07 03 other fuels (including mixtures)

14 06 03 other solvents and solvent mixes

Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

UN number: 1993

#### Transport by road/by rail (ADR/RID)

UN proper shipping name: UN 1993 FLAMMABLE LIQUID, N.O.S. (XYLENES,ETHYLBENZENE) (SPECIAL PROVISION 640E)  
 Transport hazard class(es): 3  
 Packing group: III  
 Classification code: F1  
 LQ (ADR 2011): 5 L  
 LQ (ADR 2009): 7  
 Environmental hazards: Not applicable  
 Tunnel restriction code: D/E



#### Transport by sea (IMDG-code)

UN proper shipping name: FLAMMABLE LIQUID, N.O.S (XYLENES,ETHYLBENZENE)  
 Transport hazard class(es): 3  
 Packing group: III  
 EmS: F-E, S-E  
 Marine Pollutant: n.a  
 Environmental hazards: Not applicable



#### Transport by air (IATA)

UN proper shipping name: Flammable liquid, n.o.s (XYLENES,ETHYLBENZENE)  
 Transport hazard class(es): 3  
 Packing group: III  
 Environmental hazards: Not applicable



### Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions: Yes

Page 11 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 24.01.2013 / 0002  
 Replaces revision of / Version: 25.04.2012 / 0001  
 Valid from: 24.01.2013  
 PDF print date: 24.01.2013  
 Dieselpartikelfilter Schutz 250 mL Art.: 5148

Comply with trade association/occupational health regulations.  
 Observe youth employment law (German regulation).  
 Observe law on protection of expectant mothers (German regulation).  
 VOC (1999/13/EC): ~ 100%

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections: 3, 8, 11, 12, 14

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

- 10 Flammable.
- 11 Highly flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 22 Harmful if swallowed.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Flam. Liq. — Flammable liquid  
 Acute Tox. — Acute toxicity - dermal  
 Skin Irrit. — Skin irritation  
 Eye Irrit. — Eye irritation  
 Acute Tox. — Acute toxicity - inhalation  
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation  
 STOT RE — Specific target organ toxicity - repeated exposure  
 Flam. Sol. — Flammable solid  
 Acute Tox. — Acute toxicity - oral

## Any abbreviations and acronyms used in this document:

AC Article Categories  
 acc., acc. to according, according to  
 ACGIH American Conference of Governmental Industrial Hygienists  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOEL Acceptable Operator Exposure Level  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT	Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV	Biological monitoring guidance value (EH40, UK)
BOD	Biochemical oxygen demand
BSEF	Bromine Science and Environmental Forum
bw	body weight
CAS	Chemical Abstracts Service
CESIO	Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC	Collaborative International Pesticides Analytical Council
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
COD	Chemical oxygen demand
CTFA	Cosmetic, Toiletry, and Fragrance Association
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
DOC	Dissolved organic carbon
DT50	Dwell Time - 50% reduction of start concentration
DVS	Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw	dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
EC	European Community
ECHA	European Chemicals Agency
EEA	European Economic Area
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ERC	Environmental Release Categories
ES	Exposure scenario
etc.	et cetera
EU	European Union
EWC	European Waste Catalogue
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
HET-CAM	Hen's Egg Test - Chorionallantoic Membrane
HGWP	Halocarbon Global Warming Potential
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
IBC (Code)	International Bulk Chemical (Code)
IC	Inhibitory concentration
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
LC	lethal concentration
LC50	lethal concentration 50 percent kill
LCLo	lowest published lethal concentration
LD	Lethal Dose of a chemical
LD50	Lethal Dose, 50% kill
LDLo	Lethal Dose Low
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute of Occupational Safety and Health (United States of America)
NOAEC	No Observed Adverse Effective Concentration

Page 13 of 13  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 24.01.2013 / 0002  
Replaces revision of / Version: 25.04.2012 / 0001  
Valid from: 24.01.2013  
PDF print date: 24.01.2013  
Dieselpartikelfilter Schutz 250 mL Art.: 5148

NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.